Mightystop - Safety Bollards providing traffic guidance equipment for protection of pedestrians and vehicles









Key Features

Simple quick installation

Hot dip galvanised for superior corrosion resistance

Suitable for new & existing installations

Wide range of sizes & finish options – heavy galv & powder coated colours

Available in surface & inground mount versions

Specifications

BOLL9009 80 NB Surface Mount

90mm diam x 900mm height

4.0mm wall 11 kg

BOLL11510 100 NB Surface Mount

115mm diam x 1000mm height

4.5mm wall 16kg

BOLL14012 125NB Surface Mount

140mm diam x 1200mm height

5.0mm wall 24kg

BOLL16513 150NB Surface Mount

165m diam x 1300mm height

5.0mm wall 30kg

Other sizes (diameters and lengths)

Top caps are galv steel, tack welded

are available on request

to post

Applications include ← Car parks & veh ← Redestrian path

Car parks & vehicle designation, protection

Pedestrian pathways

Warehouses, factories & loading bays

Building entry protection

Crash barriers

Sports, recreation & community centres

Warranty

5 years from date of purchase, subject to correct installation & maintenance

Inspection & Maintenance

Visual inspection for any damage or loose fittings should be carried out periodically. Basic care & maintenance is recommended

Technical Data

Body & base Steel – C250 grade, continuous weld – base plate to post Reflective tape (optional) Choice of Brilliant White or Red – class 2 (AS1906 compliant)

Protective coating Heavy hot dip galv, plus powder coating (optional) – safety yellow, other colours on special order

Base plate 200 x 200 x 10mm, 4 holes, heavy hot dip galvanised

Fixings M12 x 100 screw or expanding anchor bolt – concrete surface mount



Kwikclamp Systems